



Modem RTC 56K pour SPC

Le modem SPCN110 de Vanderbilt permet de transmettre des événements vers des centres de télésurveillance par le biais d'une ligne téléphonique analogique

Key Features

- Transmission d'alarme**
 Ce module permet à la centrale de communiquer avec un centre de télésurveillance, et d'y transmettre ses alarmes en utilisant les protocoles SIA, Contact ID ou le protocole IP FlexC en établissant une connexion PPP avec un point d'accès Internet bas débit. Le modem SPCN110 peut être utilisé en tant que transmetteur principal ou en tant que secours de la transmission TCP/IP.
- Montage et configuration facile**
 La carte modem s'enfiche directement sur la carte principale de la centrale SPC et prend directement son alimentation de la centrale, seule la ligne téléphonique est à raccorder. Le paramétrage du transmetteur s'effectue directement via le menu du clavier ou de la page Web intégrée à la centrale.
- Supervision de la ligne téléphonique**
 Le modem SPCN110 intègre un circuit de supervision de la ligne téléphonique qui indique à la centrale que la ligne est coupée, permettant ainsi de transmettre cette information via le moyen de secours (GSM) ou de déclencher la sirène de secours en cas d'alarme (option de la fonction sirène).

Operations

- SIA
- CID
- FlexC IP bas débit
- Supervision de la ligne



Technical Data

Electriques et mécaniques

Dimensions (L x H x P)	90 x 38 x 25 mm
Intensité de fonctionnement	Max. 35 mA (communication active)
Température de fonctionnement	-10 ~ +50 °C
Courant de fonctionnement optimal	Max. 25 mA à 12 Vcc

Fonctionnelles

Réseau géré	RTC (réseau téléphonique analogique)
-------------	--------------------------------------

General

Montage	Sur la carte mère des centrales SPC
Poids	0.030 kg

Ordering Data

Type	Art. No.	Description	Weight*
Modem	V54550-B101-A100	SPCN110.000 PSTN module	0.030 kg

* Total weight of the product inclusive of the weight of its accessories and packaging.

Additional Ordering Data

Acre intrusion Panels

Type	Art. No.	Description
SPC6350.320-L1	V54541-C118-A100	Acre intrusion control panel, 16-512 zones, Ethernet, G5 metal housing
SPC6330.320-L1	V54541-C105-C100	Acre intrusion control panel, 8-512 zones, Ethernet, G3 metal housing
SPC5350.320-L1	V54541-C117-A100	Acre intrusion control panel, 16-128 zones, Ethernet, G5 metal housing
SPC5330.320-L1	V54541-C107-B100	Acre intrusion control panel, 8-128 zones, Ethernet, G3 metal housing
SPC5320.320-L1	V54541-C106-B100	Acre intrusion control panel, 8-128 zones, Ethernet, G2 metal housing
SPC4320.320-L1	V54541-C109-B100	Acre intrusion control panel, 8-32 zones, Ethernet, G2 metal housing
SPC4320.220-L1	V54541-C114-A100	Acre intrusion control panel, 8-32 zones, Ethernet, G2 housing with metal base and plastic cover

Keypads

Type	Art. No.	Description
SPCK520.100-N	V54543-F115-A100	Compact Keypad with graphical display and audio
SPCK521.100-N	V54543-F116-A100	Compact Keypad with graphical display, card reader and audio
SPCK620.100	V54543-F110-A100	LCD keypad with graphical display
SPCK623.100	V54543-F111-A100	LCD keypad with graphical display, card reader and audio
SPCK420.100	V54543-F101-A100	LCD keypad with 2 x 16 characters
SPCK421.100	V54543-F102-A100	LCD keypad with 2 x 16 characters and integrated card reader

Detectors

Type	Art. No.	Description
PDM-I12	V54530-F114-A100	MAGIC PIR detector, 12m wide angle
PDM-I18	V54530-F106-A100	MAGIC PIR detector, 18 m wide angle
MK-1400	V54536-F101-A100	Magnetic contact

Accessories

Type	Art. No.	Description
IPAW8-10	V54538-F107-A100	Wireless personal alarm
IRCW6-11	V54543-F109-A100	SiWay remote control, white replaceable battery
IPAW6-10	V54538-F108-A100	Wireless Personal Alarm Button

Expanders

Type	Art. No.	Description
SPCE452.100	V54542-F107-A100	Expander with 8 outputs, back tamper
SPCE652.100	V54542-F106-A100	Expander with 8 inputs and 2 outputs, back tamper
SPCA210.100	V54547-A101-A100	2-door expander
SPCP432.300	V54545-C103-A100	Smart PSU with 2-door expander, G2-housing
SPCP433.300	V54545-C104-A100	Smart PSU with 2-door expander, G3-housing
SPCE110.100	V54542-F104-A100	Keyswitch expander with 2 LEDs and 3-position key switch
SPCE120.100	V54542-F105-A100	Indication expander with 16 LEDs, 4 function keys and integrated card reader
SPCW130.100	V54554-F101-B100	SiWay RF-expander
SPCP332.300	V54545-C102-A100	Smart PSU with 8 inputs and 2 outputs, G2-housing
SPCP333.300	S54545-C101-A100	Smart PSU with 8 inputs and 2 outputs, G3-housing
SPCP355.300	S54545-C105-A100	Smart PSU with 8 inputs and 6 outputs, G5 metal housing

Verification

Type	Art. No.	Description
SPCV340.000	V54542-F108-B100	Audio expander with 4 inputs and 1 output
SPCV341.000	V54542-F109-B100	Audio expander with 4 inputs and 1 line output
SPCV310.000	V54542-F120-A100	Audio satellite
SPCV440.000	V54542-F118-A100	Combi audio expander for MAGIC motion detectors with 4 inputs and 1 output
SPCV410.000	V54542-F119-A100	Combi audio satellite for MAGIC motion detectors
CCMS2010-IR	S54561-C112-A100	1/2.7" 2MP Compact IP Camera PoE(LAN)

Access

Type	Art. No.	Description
AR6181-MX	6FL7170-8BK	Multi-technology card reader
PP500-EM	V54501-F1-A1	Heavy-duty card and PIN reader
AR6182-RX	6FL7170-8AE	Multi-technology card and PIN reader